

RESIDENTIAL LINE

Multi-Split Air Conditioning Duct Type Indoor Units

LOW STATIC PRESSURE DUCT

Duct Type Multi-Split Unit, it is silent and allows for a perfect blend in any environment. Optimal air distribution with the user's comfort in mind. Wired control and condensates pump included.

Wall control included (NPGA/19)



To better understand this symbols refer to page 9.

DUCT-CONNECTED Multi-split Line			MD09 GA UI	MD12 GA UI	MD18 GA UI	MD24 GA UI
Power Supply (OU)			220-240V~50Hz, 1Ph			
Cooling	Cooling Capacity	kW	2.5	3.5	5.0	7.1
	Input Power	W	75	65	80	110
	Current Input	A	0.3	0.3	0.5	0.6
Heating	Heating Capacity	kW	2.8	3.9	5.5	8.0
	Input Power	W	75	65	80	110
	Current Input	A	0.3	0.3	0.5	0.6
Indoor Unit Air Flow (máx/med/min)		m³/h	450/350/280	550/400/300	700/600/500	1000/750/550
Noise Level		dB(A)	37/34/31	39/35/32	41/36/33	42/37/34
Dimensions (WxDxH)		mm	700x615x200	700x615x200	900x615x200	1100x615x200
Unit's Weight		Kg	21	22	26	30
Connections Refrigerant	Liquid/Gas Line	inch	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
Static Pressure Available		Pa	5	5	5	5
Draining Pipe Diameter		mm	ø25	ø25	ø25	ø25
Electric Connections		mm²	4x1.5			
Code			NI0145209	NI0145212	NI0145218	NI0145224

HIGH STATIC PRESSURE CONDUIT

Multi-Split high-pressure conduit with silent operation, allowing perfect integration into any environment. The condensation drainage system is possible in different directions, depending on the desired installation. The equipment withstands up to 125 Pa of static pressure. Wire control and condensate pump included.

Wall control included (NPGA/44)



To better understand this symbols refer to page 9.

DUCT-CONNECTED Multi-split Line			MDH09 GA UI	MDH12 GA UI	MDH18 GA UI	MDH24 GA UI
Cooling	Cooling Capacity	kW	2.65	3.5	5.0	7.0
Heating	Heating Capacity	kW	2.8	4.0	5.5	8.0
Indoor Unit Air Flow (máx/med/min)		m³/h	700/670/640/610/580/550/520	650/560/520/480/450/410/380	880/840/810/790/770/750/730	1500/1200/1200/1000/1000/900/900
Noise Level		dB(A)	41/39/38/37/36/35/34	39/37/36/35/34/33/32	41/39/39/38/38/37/34	45/40/40/38/38/36/36
Dimensions (WxDxH)		mm	710x450x200	710x450x200	1010x450x200	900x655x260
Power Supply (OU)			220-240V~50Hz, 1Ph			
Unit's Weight		Kg	18.5	19	25	31
Connections Refrigerant	Liquid/Gas Line	inch	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"
Static Pressure Available		Pa	25 (Máx 60Pa)	25 (Máx 60Pa)	25 (Máx 60Pa)	25 (Máx 125Pa)
Draining Pipe Diameter		mm²	ø26	ø26	ø26	ø26
Electric Connections		mm	4x1.5			
Code			NI0145409	NI0145412	NI0145418	NI0145424