

COMMERCIAL LINE

Mono-Split Air Conditioning Magnum Floor Standing



The MAGNUM Floor Standing Unit is ideal for large open spaces with tall ceilings or glass walls. It was design in order to accommodate the heating and cooling needs while keeping comfort and efficiency to the fullest, despite the hard room acclimation conditions. Has a SEER coefficient of 6,1 and an broad temperature working range. With a built-in LED panel and a minimalistic design that blends with any room kind.

An easy to access filter guarantees an effective cleaning and straightforward maintenance. The built-in Wi-Fi turns it into a user-friendlier device, just as it's easy to access filter design.



To better understand this symbols refer to page 9.

| MAGNUM FLOOR STANDING MONO-SPLIT | | XM24 GA* | XM42 GA* | XM42 GA3* | |
|------------------------------------|----------------------|-------------------|-----------------------|-----------------------|-----------------------|
| Cooling | Cooling Capacity | kW | 7.2 | 12.5 | 12.5 |
| | Power Input | W | 2050 | 4200 | 3440 |
| | Current Input Max. | A | 18 | 22 | 10 |
| | SEER | W/W | 6.1 | 5.6 | 6.1 |
| | Energy Class | | A++ | A+ | A+ |
| Heating | Heating Capacity | kW | 7.9 | 13.5 | 13.5 |
| | Power Input | W | 2330 | 4200 | 3300 |
| | Current Input Max. | A | 18 | 22 | 10 |
| | SCOP | W/W | 5.1 | 4.7 | 5.1 |
| | Energy Class | | A+ | A | A |
| Cooling Range Temperature | | °C | -15 ~ 43 | -15 ~ 43 | -15 ~ 48 |
| Heating Range Temperature | | °C | -15 ~ 24 | -15 ~ 24 | -15 ~ 24 |
| Power Supply Cable UE | | mm ² | 3x2.5 | 3x2.5 | 5x2.5 |
| Power Supply (OU) | | | 220-240V ~ 50Hz, 1Ph | | 380-400V ~ 50Hz, 3Ph |
| Electrical Connections OU/IU | | mm ² | 4x2.5 mm ² | 4x2.5 mm ² | 4x2.5 mm ² |
| Number of Fans (OU) | | | 1 | 1 | 1 |
| Compressor Type | | | INVERTER ROTARY | | |
| Indoor Unit Air Flow (max/med/min) | | m ³ /h | 750-1250 | 1580-2000 | 1800-2400 |
| Outdoor Unit Air Flow (max) | | m ³ /h | 3200 | 6000 | 2000 |
| Noise Level (IU) | | dB(A) | 35-45 | 48-53 | 51-57 |
| Indoor unit | Dimensions (WxDxH) | mm | 507x320x1770 | 587x394x1882 | 587x394x1882 |
| | Unit's Weight | Kg | 38 | 55 | 57 |
| Noise Level (OU) | | dB(A) | 61 | 64 | 69 |
| Outdoor unit | Dimensions (WxDxH) | Mm | 965x396x700 | 1028x530x822 | 1028x530x822 |
| | Unit's Weight | Kg | 53.5 | 89 | 94 |
| Carga de Refrigerante R32 | | g | 1600 | 3500 | 3500 |
| R32 Refrigerant Gas Load | | g/m | 40 | 50 | 40 |
| Refrigerant Connections | Liquid/Gas Line | in. | 1/4" - 5/8" | 3/8" - 5/8" | 3/8" - 5/8" |
| | Line Max Length | m | 25 | 30 | 30 |
| | Line Max Height Dif. | m | 10 | 20 | 20 |
| O.U. Code | | | NI0160112 | NI0160118 | NI0160118 |
| I.U. Code | | | NI0180212 | NI0180218 | NI0180218 |
| Code | | | NI0188224 | NI0188242 | NI0188243 |



* 3 years full warranty + 2 years warranty only parts

*Check availability and delivery time.